

Surface Mount General Rectifier in DO-214AC/SMA

Features

- Glass passivated chip
- For surface mounted applications
- Low reverse leakage
- Built-in strain relief, ideal for automated placement
- High forward surge current capability



Mechanical Data

- **Case:** DO-214AC/SMA (plastic package).
RoHS compliant
- **Molding Compound Flammability Rating:**
UL 94 V-0
- **Terminals:** High temperature soldering guaranteed:
260 °C/10 sec. at terminals

Applications

- Computers
- Telecom system
- Industrial equipments
- Consumer electronic applications

Absolute Maximum Ratings


Ratings at 25 °C, ambient temperature unless otherwise specified




| Parameter | Symbol | Value | Unit |
|---|----------|-------------|------|
| Maximum repetitive peak reverse voltage | VRRM | 2000 | V |
| Maximum RMS voltage | VRMS | 1400 | V |
| Maximum DC blocking voltage | VDC | 2000 | V |
| Maximum average forward rectified current at TL=110°C | I(AV) | 1 | A |
| Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC Method) | IFSM | 30.0 | A |
| Maximum instantaneous forward voltage at 1.0A | VF | 1.1 | V |
| Maximum DC reverse current at rated DC blocking voltage | IR | 5.0 50.0 | uA |
| Typical junction capacitance | CJ | 15 | pF |
| Typical thermal resistance | RqJA | 75 | °c/w |
| Operating junction and storage temperature range | TJ, TSTG | -65 to +150 | °C |

Notes:

1. Non-repetitive current pulse, per Fig.5 and detailed above TA=25°C per Fig.1
2. Measured on 8.3ms single half sine-wave, or equivalent square wave, duty cycle=4 pulses per minute maximum

Typical Characteristics ($T_{amb} = 25\text{ }^{\circ}\text{C}$ unless otherwise specified)



Package Dimensions

PAD Dimensions

Packing Information

Ordering information

| Order code | Package | Packaging option | Base quantity | Packaging specification |
|------------|--------------|------------------|----------------|-------------------------|
| M20 | DO-214AC/SMA | Tape and reel | 5000pcs / reel | EIA STD RS-481 |

Revision history

| Date | Revision | Changes |
|-------------|----------|-----------------|
| 23-May-2016 | 1.0 | Initial release |
| 21-May-2019 | 2.0 | Update |

CAUTION / WARNING

Information in this document is believed to be accurate and reliable. However, CREATEK does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information.

Users should independently evaluate the suitability of and test each product selected for their own applications, and CREATEK assumes no liability whatsoever relating to the choice, selection or use of the CREATEK products and services described herein.

CREATEK reserves the right to change or update, without notice, any information contained in this publication; to change, without notice, the design, construction, processing, or specification of any product; and to discontinue or limit production or distribution of any product.

Information in this document supersedes and replaces all information previously supplied.

Products are not designed, authorized or warranted to be suitable for use in medical, military, aircraft, space or life support equipment, nor in applications where failure or malfunction of an CREATEK product can reasonably be expected to result in personal injury, death or severe property or environmental damage. CREATEK accepts no liability for inclusion and/or use of CREATEK products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.


This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from national authorities.

Resale of CREATEK products with provisions different from the statements and/or technical features set forth in this document shall immediately void any warranty granted by CREATEK for the CREATEK product or service described herein and shall not create or extend in any manner whatsoever, any liability of CREATEK.

CREATEK expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. CREATEK only obligations are those in the CREATEK Standard Terms and Conditions of Sale and in no case will CREATEK be liable for any incidental, indirect, or consequential damages arising from the sale, resale, use, or misuse of its products.

Specifications are subject to change without notice

© Copyright 2009, CREATEK Microelectronics

 CREATEK® is a registered trademark of CREATEK Microelectronics

All rights reserved